

GOSIGHT INSTALLATION

Checklist

- Ensure the dashboard camera is installed following the guidelines in the GoSight Installation Manual.

Verify that the camera is properly powered on.

- Check that the power cables are securely attached to the fuse box, and ensure the connections of the specified cables are correctly inserted one into the other.



- Make sure the SIM and SD cards are correctly inserted.

- Turn off the vehicle and wait until the lights turn off before turning it back on. After waiting 2 minutes, proceed to verify the camera LEDs' status.

COLOR	MEANING	LED STATUS	STATUS
RED	POWER	STAY ON	POWERED; ACC. ON
		BLINKS EVERY 10 SECONDS	STANDBY; ACC. CURRENT OFF
		OFF	NO POWER SUPPLY
GREEN	GPS	STAY ON	NORMAL GPS SIGNAL
		BLINKS EVERY 10 SECONDS	SEARCHING FOR SATELLITE NETWORK
		OFF	STANDBY; ACC. POWER OFF
BLUE	SIM CARD	STAY ON	NETWORK IN OPTIMAL CONDITION.
		BLINKS EVERY 10 SECONDS	NETWORK PROBLEM OR NO SIM CARD
		OFF	STANDBY; ACC. CURRENT OFF

A successful start is normally signaled by a solid blue and red LED, a flashing green LED and a beep.

- Check the installation by viewing the live preview. Adjust lens if necessary.

Keep the ignition ON and log into your MyGeotab account. In the GoSight tab under the configuration section, find the blue camera icon  next to the camera's serial and unit number. Click this icon to view the camera's live feed.

If access to the database is not available to you, request that your designated contact perform the view check for you.



IF YOU HAVE ANY QUESTIONS, PLEASE CALL US AT 1-888-299-8555.